

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
31 May 2001 (31.05.2001)

PCT

(10) International Publication Number
WO 01/38693 A1

(51) International Patent Classification⁷: E21B 29/10,
43/10

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HEIJNEN, Wilhelmus, Hubertus, Paulus, Maria** [—/NL]; Grote Hout of Koningsweg 49, NL-Velsen 1951 GN (NL).

(21) International Application Number: PCT/EP00/12024

(81) Designated States (national): NO, US.

(22) International Filing Date:
29 November 2000 (29.11.2000)

(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
99309532.2 29 November 1999 (29.11.1999) EP


Published:

- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

(71) Applicant (for all designated States except US): **SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V.** [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PIPE EXPANSION DEVICE



(57) Abstract: A device (1) for expanding a pipe comprising a bi-conical sleeve (3) having a first section (5) and a second section (11), which sections (5, 11) are provided with at least two longitudinal guide channels (20), first wedges (25), wherein each first wedge (25) tapers into the direction in which the first section (5) widens and is provided with a support element (26) that co-operates with the corresponding longitudinal guide channel of the first section (5), second wedges (30), wherein each second wedge (30) tapers into the direction in which the second section (11) widens and is provided with a support element (31) that co-operates with the corresponding longitudinal guide channel (20) of the second section (11), and means for moving the wedges (25, 30) into each other.

WO 01/38693 A1

PIPE EXPANSION DEVICE

The present invention relates to a device for expanding a pipe, such as a casing string or a liner in a borehole. Pipe expansion is done to increase the diameter of a pipe, this is particular relevant to a well completion, wherein a number of casing strings is introduced into a borehole to protect the borehole from collapsing and to contain the well fluids therein. In such a completion each next casing string has a smaller diameter than the preceding one, in order that the next casing string can be put in place. Consequently the cross-section available to fluid flow through the completion becomes smaller and smaller as the number of casing strings increases. And this adversely affects the production from the well. To overcome this the casing strings are expanded so that the overall internal diameter of the well completion is not reduced.

Pipe expansion is achieved by displacing through the pipe an expansion device having a larger diameter than the inner diameter of the pipe. Because the forces exerted on the expansion device during pipe expansion are large, such expansion devices have fixed dimensions. And this implies that the expansion has to be performed in stages.

It is an object of the present invention to provide a device for expanding a pipe to the same diameter as the pipe through which the pipe to be expanded is run. It is a further object of the present invention to provide a device of which outer diameter can easily be adjusted, and that is sufficiently strong to withstand the forces that it subjected to during the pipe expansion.

To this end the device for expanding a pipe according to the present invention comprises a bi-conical sleeve having a first section widening from one end of the bi-conical sleeve to the middle and a second section widening from the opposite end of the bi-conical sleeve to the middle, which sections are provided with at least two longitudinal guide channels which guide channels in the second section are staggered in relation to the guide channels in the first section, a set of first wedges, wherein each first wedge tapers into the direction in which the first section widens and is provided with a support element that co-operates with the corresponding longitudinal guide channel of the first section, a set of second wedges, wherein each second wedge tapers into the direction in which the second section widens and is provided with a support element that co-operates with the corresponding longitudinal guide channel of the second section, and means for moving the sets of wedges into each other.

The invention will now be described by way of example in more detail with reference to the accompanying drawing, wherein

Figure 1 shows schematically a longitudinal section of the device according to the present invention in an initial position and in an expanded position; and

Figure 2 shows a cross-section along line II-II of Figure 1 drawn to a different scale.

Reference is made to the Figures. The device 1 for expanding a pipe (not shown) according to the present invention comprises a bi-conical sleeve 3. The bi-conical sleeve 3 consists of two sections, a first section 5 widening from one end 6 of the bi-conical sleeve 3 to the middle 10 and a second section 11 widening from the opposite end 12 of the bi-conical sleeve 3 to the middle 10.

Each of the sections 5 and 11 is provided with four longitudinal guide channels 20, distributed evenly about the circumference of the sections of the bi-conical sleeve 3. For reasons that will be explained below, the guide channels 20 in the second section 11 are staggered in relation to the guide channels (not shown) in the first section 5.

The device 1 further comprises a set of first wedges 25, wherein each first wedge 25 tapers into the direction in which the first section 5 of the bi-conical sleeve 3 widens. Each of the first wedges 25 is provided with a support element 26 that co-operates with the corresponding longitudinal guide channel of the first section 5.

The device 1 further comprises a set of second wedges 30, wherein each second wedge 30 tapers into the direction in which the second section 11 of the bi-conical sleeve 3 widens. Each of the second wedges is provided with a support element 31 that co-operates with the corresponding longitudinal guide channel 20 of the second section 11.

The reason that the guide channels 20 in the second section 11 are staggered in relation to the guide channels (not shown) in the first section 5, is that the wedges 25 and 30 can slide with respect to each other as the fingers of two hands when the hands are moved into each other.

The device 1 further comprises means for moving the sets of wedges 25 and 30 into each other. These means comprise a front end part 40, a connection rod 41 secured with one end in the front end part 40 and provided at the other end with a screw thread 45. At the other end of the device 1, the means comprise a ring 46 and a nut 47 co-operating with the screw thread 45 on the connection rod 41.

When the device 1 is being put in place in the pipe (not shown) to be expanded, the nut 47 is at the end of the connection rod 41. This position is shown in the upper half of Figure 1. In this running position, the
5 outer diameter of the device 1 is so that the device 1 can be displaced through the pipe.

In order to expand the pipe, torsion is applied on the nut 47, so that it is rotated in a direction so that the nut 47 moves towards the front end part 40 over the
10 screw threads. The tapering wedges 25 and 30 are pushed by the ring 46 into each other, and the support elements 26 and 31 move towards each other in the longitudinal guide channels. Because the longitudinal
15 guide channels are parallel to the outer surface of sections of the bi-conical sleeve 3 in which the guide channels are arranged, the support elements also move outwards in a radial direction. And consequently the
wedges 25 and 30 move outwards as well. This expanded position is shown in the lower half of Figure 1.

20 In this expanded position the device 1 can be pushed through the pipe, for example by means fluid pressure exerted on a piston (not shown) that acts on the ring 46.

The tapering wedges 25 and 30 are in contact with each other along their edges. Therefore the tapering
25 wedges 25 and 30 support each other, and in this way sufficient support is provided so that the device according to the present invention provides sufficient collapse resistance to withstand the forces that it
30 subjected to during the pipe expansion. Moreover, the outer diameter of the device can easily be adjusted.

To prevent the device 1 from expanding too far, the bi-conical sleeve 4 can be provided with a ring 50 in the
middle 10.

By adjusting the nut 47, the diameter can be
35 adjusted, and this can easily be done without removing

the device from the pipe.

It will be understood that there is a one-to-one relationship between the wedges and the guide channels, because for each tapering wedge there is a guide channel.

5 Suitably the number of guide channels, and consequently wedges is in the range of from 2 to 8, and suitably in the range of from 4 to 6. By selecting the number of wedges, the device according to the present invention can be made is sufficiently strong to withstand
10 the forces that it subjected to during the pipe expansion.

C L A I M S

1. A device for expanding a pipe, which device comprises a bi-conical sleeve having a first section widening from one end of the bi-conical sleeve to the middle and a second section widening from the opposite end of the bi-conical sleeve to the middle, which sections are provided with at least two longitudinal guide channels which guide channels in the second section are staggered in relation to the guide channels in the first section, a set of first wedges, wherein each first wedge tapers into the direction in which the first section widens and is provided with a support element that co-operates with the corresponding longitudinal guide channel of the first section, a set of second wedges, wherein each second wedge tapers into the direction in which the second section widens and is provided with a support element that co-operates with the corresponding longitudinal guide channel of the second section, and means for moving the sets of wedges into each other.
2. Device according to claim 1, wherein the sections are provided with between two and eight longitudinal guide channels.

Fig.1.





Fig.2.



INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/12024

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 E21B29/10 E21B43/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E21B B21D C21D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 146 331 A (YARNELL IAN ROLAND) 26 June 1985 (1985-06-26) abstract; figure 1	1,2
A	EP 0 418 620 A (MASTER IND INC) 27 March 1991 (1991-03-27) abstract; figures 1-3	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

4 April 2001

Date of mailing of the international search report

12/04/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Tompouloglou, C

INTERNATIONAL SEARCH REPORT

information on patent family members

Inter. Jnal Application No

PCT/EP 00/12024

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0146331 A	26-06-1985	AT 27017 T	15-05-1987
		AU 580572 B	19-01-1989
		AU 3680684 A	20-06-1985
		CA 1247869 A	03-01-1989
		DE 3463535 D	11-06-1987
		DK 600184 A,B,	17-06-1985
		FI 844875 A,B,	17-06-1985
		GB 2151325 A,B	17-07-1985
		NO 845012 A,B,	17-06-1985
		US 4789268 A	06-12-1988
		US 4657436 A	14-04-1987
		ZA 8409713 A	28-08-1985
EP 0418620 A	27-03-1991	US 4993755 A	19-02-1991
		AU 625609 B	16-07-1992
		AU 6130090 A	28-03-1991
		CA 2025655 A	23-03-1991
		JP 3121396 A	23-05-1991



INVESTOR IN PEOPLE

Application No: GB 0321157.0
 Claims searched: 1-13, 42-44

Examiner: Alan Jones
 Date of search: 9 December 2003

Patents Act 1977 : Search Report under Section 17

Documents considered to be relevant:

Category	Relevant to claims	Identity of document and passage or figure of particular relevance	
X, E	1, 4, 42 at least	GB 2388137 A	(E2TECH LTD) see eg. radially expandable members 22
X, P	1, 3, 42 at least	GB 2383361 A	(WEATHERFORD LAMB) see eg. radially expandable members 26
X	1, 3, 42 at least	GB 2086282 A	(KOTTHAUS & BUSCH) see e.g. page 2 lines 92-98, & page 2 lines 65-70
X	1, 4, 42 at least	WO 2001/038693 A1	(SHELL INT.) see e.g. radially expandable members 25, 30
X	1, 3, 42 at least	WO 2000/037766 A1	(ASTEC DEV) see e.g. radially expandable members 116

Categories:

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.

Field of Search:

Search of GB, EP, WO & US patent documents classified in the following areas of the UKC^v:

E1F, B3J

Worldwide search of patent documents classified in the following areas of the IPC⁷:

E21B, B21D

The following online and other databases have been used in the preparation of this search report:

Online: WPI, EPODOC, JAPIO

THIS PAGE BLANK (USPTO)